



Derako International B.V. Kanaalkade 66 1756 AD 't Zand NETHERLANDS Eurofins Product Testing Denmark A/S Smedeskovvej 38 8464 Galten Denmark

CustomerSupport@eurofins.com www.eurofins.com

VOC EMISSION TEST REPORT Indoor Air Comfort

6 December 2023

1 Sample Information

Sample name Solid Wood System Derako

Batch no. Emissietest Eurofins

Stated production date 01/09/2023

Product type Wood based panel

Stated thickness, mm -

Sample reception 08/09/2023

2 Brief Evaluation of the Results

Regulation or protocol	Conclusion	Version of regulation or protocol
French VOC Regulation	PRISCORE DANS LINE INTERECE	Decree of March 2011 (DEVL1101903D) and Arrêté of April 2011 (DEVL1104875A) modified in February 2012 (DEVL1133129A)
French CMR components	Pass	Regulation of April and May 2009 (DEVP0908633A and DEVP0910046A)
Italian CAM Edilizia	Pass	DM 23 giugno 2022 n. 256, GURI n. 183 del 6 agosto 2022
ABG/AgBB	Fail	Ausschuss zur gesundheitlichen Bewertung von Bauprodukten (June 2021)
Belgian Regulation	Pass	Royal decree of May 2014 (C-2014/24239)
Indoor Air Comfort	Pass	Indoor Air Comfort 9.0 of June 2023

Full details based on the testing and direct comparison with limit values are available in the following pages Regarding pass/fail decision rule please see appendix

Rasmus Verdier Analytical Service Manager





Table of contents

1		Sample Information	1
2		Brief Evaluation of the Results	1
3	3.1 3.2	Applied Test Methods General Test References Specific Laboratory Sampling and Analyses	3 3 3
4	4.1 4.2 4.3 4.4 4.5	Test Parameters, Sample Preparation and Deviations VOC Emission Chamber Test Parameters Preparation of the Test Specimen Picture of Sample Deviations from Referenced Protocols and Regulations Air Samplings from the Test Chamber	2 2 2 5 5
5	5.1 5.2	Results VOC Emission Test Results after 3 Days VOC Emission Test Results after 28 Days	6 6 8
6	6.1 6.2 6.3 6.4 6.5 6.6	Summary and Evaluation of the Results Comparison with Limit Values of the French VOC Regulation Comparison with Limit Values of the CMR Components Comparison with Limit Values of the Italian CAM Regulation Comparison with Limit Values of AgBB/ABG Comparison with Limit Values of Indoor Air Comfort Comparison with Limit Values of the Belgian Regulation	10 10 10 11 12 12
7	7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9 7.10	Appendices Chromatogram of VOC Emissions after 3 Days Chromatogram of VOC Emissions after 28 Days Sampling Report How to Understand the Results Applied LCI and NIK Values Description of VOC Emission Test Quality Assurance Accreditation Uncertainty of the Test Method Decision Rules	14 14 15 17 18 20 22 22 22 22
	7 11	Version History	22





3 Applied Test Methods

3.1 General Test References

Regulation, protocol or standard	Version	Reporting limit VOC [µg/m³]	Calculation of TVOC	Combined uncertainty ⁿ [RSD(%)]
EN 16516	2017 + A1:2020	5	Toluene equivalents	22%
ISO 16000 -3 -6 -9 -11	2006-2022 depending on part	2	Toluene equivalents	22%
ASTM D5116-10	2010	-	-	-
Specifications Indoor Air Comfort Gold	9.0 of June 2023	5	Toluene equivalents	22%
French VOC Classes	Decree of 03/2011 (DEVL1101903D) and arrêté of 02/2012 (DEVL1133129A)	2	Toluene equivalents	22%
French CMR	Regulation of April and May 2009 (DEVP0908633A and DEVP0910046A)	1	Toluene equivalents	22%
Italian CAM Edilizia	Decree 6 August 2022	2	Toluene equivalents	22%
AgBB (MVV TB/ABG)	June 2021 (2023/2022)	5	Compound Specific	22%
Belgian VOC	Royal decree of May 2014 (C - 2014 / 24239)	5	Toluene equivalents	22%

3.2 Specific Laboratory Sampling and Analyses

Procedure	External Method	Internal SOP	Quantification limit / sampling volume	Analytical principle	Uncertainty ^a [RSD(%)]
Sample preparation	ISO 16000-11:2006, EN 16516:2017+A1:2020, AgBB:2021, EMICODE:2022	71M549810	-	-	-
Emission chamber testing	ISO 16000-9:2006, EN 16516:2017+A1:2020	71M549811	-	Chamber and air control	-
Sampling of VOC	ISO 16000-6:2021, EN 16516:2017+A1:2020	71M549812	5 L	Tenax TA	-
Analysis of VOC	ISO 16000-6:2021, EN 16516:2017+A1:2020	71M542808B	1 μg/m³	ATD-GC/MS	10%
Sampling of aldehydes	ISO 16000-3:2022, EN 16516:2017+A1:2020	71M549812	35 L	DNPH	-
Analysis of aldehydes	ISO 16000-3:2022, EN 16516:2017+A1:2020	71M548400	3-6 µg/m³	HPLC-UV	10%
Sampling of phthalates*	ISO 16000-33:2017, MEL-09:2003	71M549812	60 L	Florisil	-
Analysis of phthalates*	ISO 16000-33:2017	71M546060	0.6 μg/m³	GC/MS	10%





4 Test Parameters, Sample Preparation and Deviations

4.1 VOC Emission Chamber Test Parameters

Parameters	Value	Sample Conditions	Value
Chamber volume, V[L]	225	Date and time of unpacking and start of sample preparation	13/09/2023 - 10:15
Air change rate, n[h-1]	0.5	Preconditioning period	-
Air Velocity [m/s]	0.1	Chamber test period	13/09/2023 - 11/10/2023
Area specific ventilation rate, q [m/h or m³/m²/h]	1.25	Analytical test period	13/09/2023 - 16/10/2023
Relative humidity of supply air, RH [%]	50 ± 3	Exposed sample area [m²]	0.090
Temperature of supply air, T [°C]	23 ± 1	Loading factor [m²/m³]	0.4
Background concentration of individual VOC's [µg/m³]	< 2	Test scenario	Flooring or ceiling
Background concentration of TVOC [µg/m³]	< 20	Sample thickness [mm]	-

4.2 Preparation of the Test Specimen

Edges and back were covered with aluminium foil and aluminium tape

4.3 Picture of Sample







4.4 Deviations from Referenced Protocols and Regulations

No deviations from the referenced test methods were observed.

4.5 Air Samplings from the Test Chamber

Sampling media	Day (yyyy-mm-dd)	Time (hh:mm)	Volume [L]
3 Day, DNPH silicagel	2023-09-16	09:55 - 11:45	37
3 Day-Res, DNPH silicagel	2023-09-16	09:57 - 11:46	36
3 Day, Tenax TA	2023-09-16	09:57 - 10:57	5.2
3 Day-Res, Tenax TA	2023-09-16	10:58 - 11:47	2.2
3 Day, Tenax TA	2023-09-16	13:40 - 13:40	0.50
28 Day, Florisil	2023-10-11	11:30 - 13:59	60
28 Day-Res, Florisil	2023-10-11	11:31 - 13:59	59
28 Day, DNPH silicagel	2023-10-11	08:07 - 09:56	36
28 Day-Res, DNPH silicagel	2023-10-11	08:07 - 09:58	36
28 Day, Tenax TA	2023-10-11	08:08 - 09:07	5.1
28 Day-Res, Tenax TA	2023-10-11	09:08 - 09:58	2.3





5 Results

5.1 VOC Emission Test Results after 3 Days

	CAS No.	Retention time	ID- Cat	Specific Conc.	Toluene eq.	Specific SER	R_D	R _B
		[min]		[µg/m³]	[µg/m³]	[µg/(m²·h)]		
VOC with NIK/LCI								
Acetic acid ^a *	64-19-7	2.07	1	2600	290	3200	2.1	2.1
1-Butanol	71-36-3	2.53	1	30	9.0	37	0.010	0.010
Pentanal	110-62-3	2.90	1	37	13	47	0.047	0.047
1,2-Propandiol (Propylene glycol) *	57-55-6	3.50	1	120	22	150	0.056	0.056
1-Pentanol *	71-41-0	4.11	2	71	71	89	0.098	0.098
Hexanal	66-25-1	4.84	1	100	52	130	0.12	0.12
1-Hexanol *	111-27-3	6.30	1	16	7.6	20	0.0077	0.0077
Heptanal	111-71-7	6.93	1	18	10	23	0.020	0.020
α-Pinene *	80-56-8	7.54	1	250	250	320	0.10	0.10
1-Heptanol *	111-70-6	8.11	1	11	6.3	14	0.0067	0.0067
β-Pinene *	127-91-3	8.27	1	12	12	15	0.0084	0.0084
Propylene carbonate *	108-32-7	8.42	1	490	71	620	0.49	0.49
Octanal	124-13-0	8.64	1	12	8.2	15	0.013	0.013
3-Carene *	13466-78-9	8.79	1	320	330	400	0.22	0.22
2-Ethyl-1-hexanol	104-76-7	9.01	1	19	14	23	0.063	0.063
Limonene *	138-86-3	9.05	1	19	19	24	0.0038	0.0038
Terpinolene *	586-62-9	9.89	1	15	18	18	0.011	0.011
Nonanal *	124-19-6	10.05	1	14	8.9	17	0.015	0.015
Butyldiglycol *	112-34-5	11.09	1	43	18	54	0.12	0.12
n-Dodecane	112-40-3	11.19	1	8.6	9.9	11	0.0014	0.0014
n-Tridecane	629-50-5	12.27	1	10	12	13	0.0017	0.0017
Other saturated aliphatic hydrocarbons C9-C16 *		7.8-13.3	2	180	180	220	0.029	0.029
Other alkylbenzenes *		8.2-9.0	2	20	20	25	0.044	0.044
VOC without NIK/LCI								
2-Heptanon *	110-43-0	6.73	2	11	11	14		
2-Pentylfurane *	3777-69-3	8.47	2	39	39	49		
Sum of VOC without NIK/LCI				50	50	63		
VVOC compounds								
Acetone *	67-64-1		1	36		45	0.0003	0.0003
TVVOC				36	< 5	45		







	CAS No.	Retention time	ID- Cat	Specific Conc.	Toluene eq.	Specific SER	R_D	R _B
		[min]		[µg/m³]	[µg/m³]	[µg/(m²·h)]		
SVOC compounds								
None determined								
TSVOC				< 5	< 5	< 7		
Carcinogens								
Total carcinogens				< 1	< 1	< 2		
Aldehydes								
Formaldehyde	50-00-0		1	< 3		< 4		
Acetaldehyde	75-07-0		1	25		31	0.084	0.084
Propionaldehyde	123-38-6		1	3.9		4.9		
Butyraldehyde	123-72-8		1	6.4		8.0	0.0099	0.0099
Acrolein *	107-02-8		1	< 5		< 7		
2-Butenal *	123-73-9		1	< 5		< 7		
Glutaraldehyde *	111-30-8		1	< 5		< 7		
R-values							3.7	3.7
TVOC				4400	1500	5600		





5.2 VOC Emission Test Results after 28 Days

	CAS No.	Retention time	ID- Cat	Specific Conc.	Toluene eq.	Specific SER	R_D	R _B
		[min]		[µg/m³]	[µg/m³]	[µg/(m²-h)]		
VOC with NIK/LCI								
Acetic acid ^a *	64-19-7	2.08	1	1000	110	1300	0.85	0.85
Pentanal	110-62-3	2.89	1	9.9	< 5	12	0.012	0.012
1,2-Propandiol (Propylene glycol) *	57-55-6	3.49	1	45	8.1	56	0.021	0.021
1-Pentanol *	71-41-0	4.09	2	26	26	33	0.036	0.036
Hexanal	66-25-1	4.82	1	31	15	39	0.034	0.034
1-Hexanol *	111-27-3	6.29	1	6.4	< 5	8.0	0.0031	0.0031
Pentanoic acid ^d *	109-52-4	6.54	1	5.5	< 5	6.8	0.0026	0.0026
Heptanal	111-71-7	6.92	1	5.8	< 5	7.2	0.0064	0.0064
α-Pinene *	80-56-8	7.52	1	160	160	210	0.066	0.066
Hexanoic acid ^d *	142-62-1	8.33	1	30	13	37	0.014	0.014
Propylene carbonate *	108-32-7	8.38	1	110	15	140	0.11	0.11
3-Carene *	13466-78-9	8.77	1	140	140	180	0.093	0.093
Limonene *	138-86-3	9.04	1	6.2	6.3	7.7	0.0012	0.0012
Terpinolene *	586-62-9	9.88	1	7.2	8.9	9.0	0.0051	0.0051
n-Tridecane	629-50-5	12.26	1	5.2	6.1	6.5	0.0009	0.0009
Other saturated aliphatic hydrocarbons C9-C16 *		8.0-13.2	2	84	84	110	0.014	0.014
Other alkylbenzenes *		8.1-9.0	2	14	14	17	0.031	0.031
VOC without NIK/LCI								
2-Pentylfurane *	3777-69-3	8.46	1	13	13	16		
Sum of VOC without NIK/LCI				13	13	16		
VVOC compounds								
None determined								
TVVOC				< 5	< 5	< 7		
SVOC compounds								
None determined								
TSVOC				< 5	< 5	< 7		
Carcinogens								
Total carcinogens				< 1	< 1	< 2		
CMR (French reg.)								
Benzene	71-43-2		1	< 1		< 2		

The analysis are carried out on the sample(s) as received and the result(s) are only valid for the tested sample(s).

This report may only be copied or reprinted in its entirety.





	CAS No.	Retention time	ID- Cat	Specific Conc.	Toluene eq.	Specific SER	R_D	R _B
		[min]		[µg/m³]	[µg/m³]	[µg/(m²·h)]		
Trichloroethylene	79-01-6		1	< 1		< 2		
Dibutylphthalate (DBP)*	84-74-2		1	< 1		< 2		
Diethylhexylphthalate (DEHP)*	117-81-7		1	< 1		< 2		
Aldehydes								
Formaldehyde	50-00-0		1	< 3		< 4		
Acetaldehyde	75-07-0		1	10		13	0.034	0.034
Propionaldehyde	123-38-6		1	< 3		< 4		
Butyraldehyde	123-72-8		1	< 3		< 4		
Acrolein *	107-02-8		1	< 5		< 7		
2-Butenal *	123-73-9		1	< 5		< 7		
Glutaraldehyde *	111-30-8		1	< 5		< 7		
R-values							1.3	1.3
TVOC				1700	630	2200		
TVOC (French label)					650			
Toluene	108-88-3			< 2	< 2	< 3		
Tetrachloroethylene	127-18-4			< 2	< 2	< 3		
Ethylbenzene	100-41-4			< 2	< 2	< 3		
Xylene	1330-20-7			< 2	< 2	< 3		
Styrene	100-42-5			< 2	< 2	< 3		
2-Butoxyethanol	111-76-2			< 2	< 2	< 3		
1,2,4-Trimethylbenzene	95-63-6			< 2	< 2	< 3		
1,4-Dichlorobenzene	106-46-7			< 2	< 2	< 3		





6 Summary and Evaluation of the Results

6.1 Comparison with Limit Values of the French VOC Regulation

	CAS No.	Conc. 28 days	EMISSIONS DANS LIAIR INTÉRIEUR	EMISSIONS DANS L'AIR INTÉRIEUR	EMISSIONS DAMS LIVIR INTÉRIEUR	EMISSIONS DANS LIAIR NITÉRIEUR A A B C
		μg/m³	µg/m³	µg/m³	µg/m³	µg/m³
TVOC	-	650	> 2000	< 2000	< 1500	< 1000
Formaldehyde	50-00-0	< 3	> 120	< 120	< 60	< 10
Acetaldehyde	75-07-0	10	> 400	< 400	< 300	< 200
Toluene	108-88-3	< 2	> 600	< 600	< 450	< 300
Tetrachloroethylene	127-18-4	< 2	> 500	< 500	< 350	< 250
Ethylbenzene	100-41-4	< 2	> 1500	< 1500	< 1000	< 750
Xylene	1330-20-7	< 2	> 400	< 400	< 300	< 200
Styrene	100-42-5	< 2	> 500	< 500	< 350	< 250
2-Butoxyethanol	111-76-2	< 2	> 2000	< 2000	< 1500	< 1000
1,2,4-Trimethylbenzene	95-63-6	< 2	> 2000	< 2000	< 1500	< 1000
1,4-Dichlorobenzene	106-46-7	< 2	> 120	< 120	< 90	< 60

The product was assigned a VOC emission class without taking into account the measurement uncertainty associated with the result. As specified in French Decree no. 2011-321 of March 23 2011, correct assignment of the VOC emission class is the sole responsibility of the party responsible for distribution of the product in the French market.

6.2 Comparison with Limit Values of the CMR Components

CMR (French reg.)	CAS No.	Conc. 28 days µg/m³	Max. allowed air concentration μg/m³
Benzene	71-43-2	< 1	<1
Trichloroethylene	79-01-6	< 1	<1
Dibutylphthalate (DBP)*	84-74-2	< 1	<1
Diethylhexylphthalate (DEHP)*	117-81-7	< 1	<1





6.3 Comparison with Limit Values of the Italian CAM Regulation

	CAS No.	Conc. 28 days μg/m³	Limit value 28 days µg/m³
TVOC	-	650	< 1500
Formaldehyde	50-00-0	< 3	< 60
Acetaldehyde	75-07-0	10	< 300
Toluene	108-88-3	< 2	< 450
Tetrachloroethylene	127-18-4	< 2	< 350
Ethylbenzene	100-41-4	< 2	< 1000
Xylene	1330-20-7	< 2	< 300
Styrene	100-42-5	< 2	< 350
2-Butoxyethanol	111-76-2	< 2	< 1500
1,2,4-Trimethylbenzene	95-63-6	< 2	< 1500
1,4-Dichlorobenzene	106-46-7	< 2	< 90
Benzene	71-43-2	< 1	< 1
Trichloroethylene	79-01-6	< 1	< 1
Dibutylphthalate (DBP)*	84-74-2	< 1	< 1
Diethylhexylphthalate (DEHP)*	117-81-7	< 1	< 1

The product was assigned a VOC emission class without taking into account the measurement uncertainty associated with the result.





6.4 Comparison with Limit Values of AgBB/ABG

Parameters	Test after 3 days		Test after 28 days	
	Concentration mg/m³	Limit Value mg/m³	Concentration mg/m³	Limit Value mg/m³
TVOC	4.4	≤ 10	1.7	≤ 1.0
TSVOC	< 0.005	-	< 0.005	≤ 0.1
R-value (dimensionless)	3.7	-	1.3	≤ 1
Sum of VOC without NIK/LCI	0.050	-	0.013	≤ 0.1
Formaldehyde	-	-	< 0.003	≤ 0.1
Total carcinogens	< 0.001	≤ 0.01	< 0.001	≤ 0.001

Compliance with the limits alone does not replace an approval or voluntary documentation by a Technical Assessment Body according to the Construction Product Regulation. This requires an application and approval.

6.5 Comparison with Limit Values of Indoor Air Comfort

	Test after 3 days		Test after 28 days	
	Concentration µg/m³	Limit Value µg/m³	Concentration µg/m³	Limit Value µg/m³
TVOC (EN 16516)	1500	≤ 10000	630	≤ 1000
TSVOC	< 5	-	< 5	≤ 100
R _D -value (NIK) (dimensionless)	3.7	-	1.3	≤ 1
R _B -value (LCI) (dimensionless)	3.7	-	1.3	≤ 1
Sum of VOC without NIK/LCI	50	-	13	≤ 100
Total carcinogens	< 1	≤ 10	-	-
Any individual carcinogens	-	-	< 1	≤ 1
CMR (French reg.)	-	-	< 1	≤ 1
Formaldehyde	< 3	-	< 3	≤ 60
Acetaldehyde	25	-	10	≤ 200
French A+/A	-	- Constant label. This	Comp	olies

Compliance with the limits alone does not entitle to use the Indoor Air Comfort label. This requires an application, site inspection, and approval. See www.eurofins.com/iac-procedures.

Wood-based materials in the form of slim oriented strand board (OSB) and resin-bonded particleboard are only evaluated agianst total carcinogens.





6.6 Comparison with Limit Values of the Belgian Regulation


Parameters	Test after 28 days		
	Concentration µg/m³	Limit Value µg/m³	
TVOC (EN 16516)	630	≤ 1000	
TSVOC	< 5	≤ 100	
R-value (dimensionless)	1.3	≤ 1	
Total carcinogens	< 1	≤ 1	
Toluene	< 5	≤ 300	
Formaldehyde	< 3	≤ 100	
Acetaldehyde	10	≤ 200	






7 Appendices

7.1 Chromatogram of VOC Emissions after 3 Days



7.2 Chromatogram of VOC Emissions after 28 Days



Please consider the different scales.





7.3 Sampling Report

Con	nbined Sampling Re	port and Chain	of Custody
Name of applicant: (name, company, phon	ir. Margot van den Bove		ional B.V., Kanaalkade 66,
	Product	information	
Name of the product:	Solid Wood System Derako		Panel, wood based
Batch N°:	Emissietest Eurofins	Article N°:	
Model / Program / Series:	Solid wooden panel with fire treatment, finish and non-woven tissue.	Manufacture: (Company, Address, Stamp)	Derako International B.V., Kanaalkade 66, 1756AD 't Zand, The Netherlands
	Production & Sa	ampling information	
Production Date: Time:	1-9-2023	Sampling Date:	: vrijdag 1 september 2023 : 14.00
Place of sampling (if deviating from the manufature)		Sample is taken from:	ongoing productionstocksretained sample
		Number of samples:	3
sampling: (Name, company,	Margot van den Bovenkamp, Derako International B.V., +31 224 59 23 56.	Signature of sample collector:	
Where has the product been stored prior to sampling?	store	How has the product been stored prior to sampling?	☐ open ☑ in the stack ☐ wrapped up
Place of storage:		Packing material:	
emissions, by solvent em any other uncertainties, c	mple was taken, by petrol nissions from production;	Cut edges are raw wood	with fire treatment (without
and identification of new exposed in the emission	surfaces and surface to be	finish).	with the treatment (without
	Confirmation fr	om the applicant	MUNICIPALITY
Herewith the signer conf		lata given above. The sar	mple was selected, drawn and

The analysis are carried out on the sample(s) as received and the result(s) are only valid for the tested sample(s).





Date:	Signature:	151 DERAKO)
6-9-2023	(Stamp)	Solid Wood 57 DERAKO INTERNATIONAL BV Kanaalkade 66, 1756 AD "I Zand Kanaalkade 66, 1756 AD "I Zand BO Box 32, 1756 ZG "I Zand W W	12 M2 All
	Chain	The Netherlands of custody	
When	never the sample is handed ov	ver, please fill out the below	information
Handed over between:	Initials + Signature	Date + Time	Condition
Handed over by	A.D.	1-sep	good
Handed over to	MvdB	1-sep	good
Handed over by			
Handed over to			
Handed over by			
Handed over to			
Laboratory receiving de package and sample, as	tails (date, condition of ssigned lab no.): 8/9/23,	not ok, 392-20	023-00418201
	ptionist, Eurofins Product Testing A/S: Signature of receptionist:		
Amalie Sorer	rsen	Sur	





7.4 How to Understand the Results

7.4.1 Acronyms Used in the Report

- < Means less than
- > Means bigger than
- * Not a part of our accreditation
- Please see section regarding uncertainty in the Appendices
- § Deviation from method. Please see deviation section
- a The method is not optimal for very volatile compounds. For these substances smaller results and a higher measurement uncertainty cannot be ruled out
- b The component originates from the substrate and is thus removed
- c The results have been corrected by the emission from the substrate
- d Very polar organic compounds are not suitable for reliable quantification using Tenax TA adsorbent and HP-5ms GC column. A high degree of uncertainty must be expected
- e The component may be overestimated due to contribution from the system
- SER Specific Emission Rate

7.4.2 Explanation of ID Category

Categories of Identity:

- 1: Identified by comparison with a mass spectrum obtained from library and supported by other information and quantified through specific calibration.
- 2: Identified by comparison with a mass spectrum obtained from library and supported by other information. Quantified as toluene equivalent.
- 3: Identified with a lower match by comparison with a mass spectrum obtained from a library. Quantified as toluene equivalent.
- 4: Not identified, quantified as toluene equivalent.





7.5 Applied LCI and NIK Values

7.5.1 LCI/NIK Values for Compounds found after 3 Day Measurements

Compound	CAS No.	AgBB 2021 NIK	Belgian NIK
		[µg/m³]	[µg/m³]
Acetic acid ^{ad *}	64-19-7	1200	1200
1-Butanol	71-36-3	3000	3000
Pentanal	110-62-3	800	800
1,2-Propandiol (Propylene glycol) *	57-55-6	2100	2100
1-Pentanol *	71-41-0	730	730
Hexanal	66-25-1	900	900
1-Hexanol *	111-27-3	2100	2100
Heptanal	111-71-7	900	900
α-Pinene *	80-56-8	2500	2500
1-Heptanol *	111-70-6	1700	1700
β-Pinene *	127-91-3	1400	1400
Propylene carbonate *	108-32-7	1000	1000
Octanal	124-13-0	900	900
3-Carene *	13466-78-9	1500	1500
2-Ethyl-1-hexanol	104-76-7	300	300
Limonene *	138-86-3	5000	5000
Terpinolene *	586-62-9	1400	1400
Nonanal *	124-19-6	900	900
Butyldiglycol *	112-34-5	350	350
n-Dodecane	112-40-3	6000	6000
n-Tridecane	629-50-5	6000	6000
Other saturated aliphatic hydrocarbons C9-C16 *		6000	6000
Other alkylbenzenes *		450	450
Acetone *	67-64-1	120000	120000
Acetaldehyde	75-07-0	300	300
Propionaldehyde	123-38-6	650	650
Butyraldehyde	123-72-8	650	650
Octanal *	124-13-0	900	900
Nonanal *	124-19-6	900	900





7.5.2 LCI/NIK Values for Compounds found after 28 Day Measurements

Compound	CAS No.	AgBB 2021 NIK	Belgian NIK
		[µg/m³]	[µg/m³]
Acetic acid ^{ad *}	64-19-7	1200	1200
Pentanal	110-62-3	800	800
1,2-Propandiol (Propylene glycol) *	57-55-6	2100	2100
1-Pentanol *	71-41-0	730	730
Hexanal	66-25-1	900	900
1-Hexanol *	111-27-3	2100	2100
Pentanoic acid ^d *	109-52-4	2100	2100
Heptanal	111-71-7	900	900
α-Pinene *	80-56-8	2500	2500
Hexanoic acid ^d *	142-62-1	2100	2100
Propylene carbonate *	108-32-7	1000	1000
3-Carene *	13466-78-9	1500	1500
Limonene *	138-86-3	5000	5000
Terpinolene *	586-62-9	1400	1400
n-Tridecane	629-50-5	6000	6000
Other saturated aliphatic hydrocarbons C9-C16 *		6000	6000
Other alkylbenzenes *		450	450
Acetaldehyde	75-07-0	300	300





7.6 Description of VOC Emission Test

7.6.1 Test Chamber

The test chamber is made of stainless steel. A multi-step air clean-up is performed before loading the chamber, and a blank check of the empty chamber is performed.

The chamber operation parameters are as described in the test method section. (EN 16516, ISO 16000-9, internal method no.: 71M549811).

The recovery rates in the climate test chamber have been investigated using toluene and n-dodecane. The mean recovery rates of toluene and n-dodecane were concluded to be between 95 % and 100 % depending on the chamber size. These values comply with the criteria of a minimum mean recovery rate of 80 % stated in the 16000-9 test method.

Air sampling from the test chamber is carried out in a clean test chamber room at ambient air pressure and 23 ± 1 °C.

7.6.2 Expression of the Test Results

All test results are calculated as specific emission rate, and as extrapolated air concentration in the European Reference Room (EN 16516, AgBB, EMICODE, M1 and Indoor Air Comfort).

7.6.3 Testing of Carcinogenic VOCs

The emission of carcinogens (EU Categories C1A and C1B, as per European law) is tested by drawing sample air from the test chamber outlet through Tenax TA tubes after the specified duration of storage in the ventilated test chamber. Analysis is performed by ATD-GC/MS (automated thermal desorption coupled with gas chromatography and mass spectroscopy using 30 m HP-5 (slightly polar) column with 0.25 mm ID and 0.25 µm film, Agilent) (EN 16516, ISO 16000-6, internal methods no.: 71M549812 / 71M542808B).

All identified carcinogenic VOCs are listed; if a carcinogenic VOC is not listed then it has not been detected. Quantification is performed using the TIC signal and authentic response factors, or the relative response factors relative to toluene for the individual compounds.

This test only covers substances that can be adsorbed on Tenax TA and can be thermally desorbed. If other emissions occur, then these substances cannot be detected (or with limited reliability only).

7.6.4 Testing of VOC, SVOC and VVOC

The emissions of volatile organic compounds are tested by drawing sample air from the test chamber outlet through Tenax TA tubes after the specified duration of storage in the ventilated test chamber. Analysis is performed by ATD-GC/MS using HP-5 column (30 m, 0.25mm ID, 0.25µm film) (EN 16516, ISO 16000-6, internal methods no.: 71M549812 / 71M542808B).

All single substances that are listed with a LCI/NIK value in the latest publications (hereafter referred to as target compounds) are identified if present. All other appearing VOCs are identified as far as possible. Quantification of target compounds is done using the TIC signal and authentic response factors, or the relative response factors relative to toluene. For certain compound groups, which differ significantly in chemistry from toluene, quantification is performed relative to a representative member of the group for more accurate and precise results. This can include quantification of for example glycols and acids. In addition to that, all results are also expressed in toluene equivalents. All non-target compounds, as well as all non-identified substances, are quantified in toluene equivalents.

The results of the individual substances are calculated in three groups depending on their retention time when analyzing using a non-polar column (HP-1):

- Volatile Organic Compounds (VOC) are defined as: All substances eluting between and including n-hexane (n-C6) and n-hexadecane (n-C16)





- Semi-Volatile Organic Compounds (SVOC) are defined as: All substances eluting after n-hexadecane (n-C16) and before and including n-docosane (n-C22)
- Very Volatile Organic Compounds (VVOC) are defined as: All substances eluting before n-hexane (n-C6).

Total Volatile Organic Compounds (TVOC) is calculated by summation of all individual VOCs with a concentration $\geq 5~\mu g/m^3$. The TVOC can be expressed either in toluene equivalents as defined in EN 16516 and similar to ISO 16000-6, or as the sum of concentrations using specific or relative response factors. In the case of summation of concentrations using authentic or relative response factors, the toluene equivalent is applied to all non-target and non-identified VOCs before summing up. Compounds regarded as VOC in line with the above definition but elute before n-C6 or after n-C16 on the HP-5 column are treated as VOC, and are thus added to the TVOC.

Total Semi-Volatile Organic Compounds (TSVOC) is calculated by the summation of all individual SVOCs expressed in toluene equivalents with a concentration $\geq 5~\mu g/m^3$, as defined in EN 16516. VOCs that are regarded as VOC in line with the above definition, but elute after n-C16 in this test, are not added to the TSVOC.

Total Very Volatile Organic Compounds (TVVOC) is calculated by the summation of all individual VVOCs with a concentration $\geq 5 \,\mu\text{g/m}^3$ and expressed in toluene equivalents. VOCs that are regarded as VOC in line with the above definition, but elute before n-C6 in this test, are not added to the TVVOC.

This test only covers substances which can be adsorbed on Tenax TA and can be thermally desorbed. If emissions of substances outside these specifications occur then these substances cannot be detected (or with limited reliability only).

7.6.5 Calculation of R Values with LCI Lists

The concentrations of detected compounds $\geq 5~\mu g/m^3$ are divided by their respective LCI/NIK value (if defined in the given publication). The sum of the quotients gives the R value, which can be mathematically expressed:

$$R = \sum_{i}^{n} \left(\sqrt[c_{i}]{NIK_{i}} + ... + \sqrt[c_{n}]{NIK_{n}} \right)$$

This R value is calculated, depending on the purpose of this test, for the European LCI list, for the German LCI/NIK list (R_D), and/or for the Belgian LCI list (R_B).

All VOCs without published LCI/NIK value and concentration \geq 5 μ g/m³ are summed up as sum of VOCs without LCI/NIK if required by the standard or protocol.

7.6.6 Testing of Aldehydes

The presence of aldehydes is tested by drawing air samples from the test chamber outlet through DNPH-coated silicagel tubes after the specified duration of storage in the ventilated test chamber. Analysis is performed by solvent desorption and subsequently by HPLC and UV-/diode array detection.

The absence of formaldehyde and other aldehydes is stated if UV detector response at the specific wavelength is lacking at the specific retention time in the chromatogram. Otherwise it is checked whether the reporting limit is exceeded. In this case the identity is finally checked by comparing full scan sample UV spectra with full scan standard UV spectra.

Conversions of specific aldehydes from µg/m³ to ppm are done by the ideal gas law using a temperature of 23 degree Celsius and standard atmospheric pressure.





7.6.7 Testing of Phthalates

The presence of phthalates is tested by drawing air samples from the test chamber outlet through tube with Florisil adsorbent after the specified duration of storage in the ventilated test chamber. Analysis is performed by solvent desorption and subsequently by GC/MS. Analysis of phthalates is not currently covered by the accreditation (Internal methods no.: 71M549812 / 71M546060).

7.7 Quality Assurance

Before loading the test chamber, a blank check of the empty chamber is performed and compliance with background concentrations in accordance with EN 16516 / ISO 16000-9 is determined.

Air sampling at the chamber outlet and subsequent analysis is performed in duplicate. Relative humidity, temperature and air change rate in the chambers is logged every 5 minutes and checked daily. A double determination is performed on random samples at a regular interval and results are registered in a control chart to ensure the uncertainty and reproducibility of the method.

The stability of the analytical system is checked by a general function test of device and column, and by use of control charts for monitoring the response of individual substances prior to each analytical sequence.

7.8 Accreditation

The testing methods described above are accredited online with EN ISO/IEC 17025 by DANAK (no. 522). This accreditation is valid worldwide due to mutual approvals of the national accreditation bodies (ILAC/IAF, see also www.eurofins.com/galten.aspx#accreditation).

Not all parameters are covered by this accreditation. The accreditation does not cover parameters marked with an asterisk (*), however analysis of these parameters is conducted at the same level of quality as for the accredited parameters.

7.9 Uncertainty of the Test Method

The relative standard deviation of the overall analysis is 22%. The expanded uncertainty Um equals 2 x RSD. For further information please visit www.eurofins.dk/product-testing/uncertainty/.

7.10 Decision Rules

Eurofins Product Testing A/S, declare statement of conformity based on the "Binary Statement for Simple Acceptance Rule" described in ILAC's "Guidelines on decision Rules and Statements of Conformity" ILAC-G8:09/2019.

This means that results above the detection limit are always reported with two significant digits. Results are evaluated with the same number of significant digits as the corresponding limit values, and conformity is based on results being less than or equal to limit values.

For limit values with more than two significant digits, the third digit will be used to confirm whether a result is below or equal to the limit value. It will always be indicated in the evaluation table if this expanded evaluation is performed.

For further information, please visit www.eurofins.dk/product-testing/om-os/beslutningsregler/

7.11 Version History

Report date	Report number	Modification
06/12/2023	392-2023-00418201_B_EN	Current version